

WSLI CIRCINUS LED UP AND DOWN LIGHTERS



FEATURES

- High efficiency light source, Epistar high power led.
- High quality Aluminum lamp fixture/lamp, Beautiful appearance and reasonable waterproof structure.
- Tempered glass as cover, heat-resisting and impact resistance.
- Supplied with 3C/0.75mm² (equal to 3C/18AWG) VDE or VDM Rubber Cable with Male and Female connector or Tinned wire tip
- Long Lifespan, up to 50000 hours.
- Waterproof IP65, outdoor use.

OPTIONS ON REQUEST

- Epistar, CREE and Bridgelux led is available for optional.
- Correlated Color Temperature (CCT) as below for optional:
Warm White (2700K-3200K), Nature White (4000K-4500K), Pure White (6000K-6500K)
RED, Green, Blue, Yellow, Amber, RGB and RGBW.
- Clear and Frosted Tempered Glass for optional.
- Housing Finish Grey, Silver and Black for optional.
- PMMA Lens with Beam Angle 5°10°15°25°30°45°60°90°120° for optional.
- Male and Female Connector or Tinned AWG wire tip for optional.
- Working Voltage DC12V, DC24V, AC100-240V is available.
- Cable lengths can be supplied according to your requirements.
- Meanwell, other Brand in China Market and Factory Self-made power supply for optional.
External power supply for light with DC12V and DC24V sold separately.
- 0/1-10V, PWM and Dali can be optional.
- 2 year to 5 years warranty for optional.

SPECIFICATION

Body size	W100*95*H200mm	Voltage	AC100-240V
Output Power	2*3W 2*6W	IP Ratio	IP65
Luminous Flux Output	80-90lm/w	Installation	Wall Surface Mounted
Rendering Index	Ra>75	Control Mode	As requested
Light Source	4000K	Connector	As requested
Finish	White	Pigtail wire	20cm
Lens	PMMA	Extra Power wire	NIL
Beam Angle	As Requested	Extra Signal Wire	NIL
Body Material	Aluminum Body	Power Supply	Embedded
Diffuser	Frosted Tempered Glass	Accessories	NIL
		Certificate	CE, RoHS
		Warranty	3 years