

WSLI-BETA-HIGH-BAY



Features

- High efficiency, up to 130lm/w. save more energy;
- High Luminous flux >up to 24,000lm
- Perfectly suitable for industrial use due to IP65.
- 50000 hours lifetime, low maintenance;
- Soft and uniform light;
- Fast and easy install;
- Rohs,CE,UL,DLC certification.
- Patent design.

Part No.	HB-60W	HB-80W	HB-150W	HB-200W
Wattage (W)	60	80	150	200
Dimmable	On-off/1-10v/Dali	On-off/1-10v/Dali	On-off/1-10v/Dali	On-off/1-10v/Dali
Lumens (lm) @6000k	7,800	10,400	19,500	26,000
CCT (K)	3000/4000/5000/6000	3000/4000/5000/6000	3000/4000/5000/6000	3000/4000/5000/6000
CRI	>80,90	>80,90	>80,90	>80,90
Beam Angle (deg)	60/90/120	60/90/120	60/90/120	60/120
Energy Efficiency Class	A	A	A	A
Voltage (V)	AC100-277V	AC100-277V	AC100-277V	AC100-277V
Lifespan(hrs)	50,000	50,000	50,000	50,000
Weight(KG)	1.5	1.8	1.8	2.0
Product dimension(mm)	φ 410*446	φ 410*446	φ 425*524	φ 425*553

